

# ADAPTER PLATE MOUNTING KIT FOR KEYSECURE® 5 & 6

KeySecure 5 and 6 can be mounted on an older KeySecure 3b or 4 bracket using the Knox Adapter Plate Kit (KLS-AP). For the best mounting option for KeySecure 5 and 6, Knox also has and recommends our new KeySecure 5 and 6 fitted brackets (60° & 90°), which have the same vehicle mounting bolt pattern as the old KeySecure bracket. There are three types of mounting brackets available: a 60° angle, a 90° angle, and a flat mount bracket. These solid steel brackets can be used for installing the KeySecure units in a vehicle or office.



Knox KeySecure 5



Knox KeySecure 6

## FEATURES

- ✓ 3/8" plate steel construction
- ✓ Black industrial powder coating
- ✓ Will mount to either an older 90° angle or 60° angle KeySecure bracket

### KNOX RAPID ACCESS SYSTEM

The Knox Company manufactures a complete line of high-security products including KnoxBox key boxes, key vaults, cabinets, key switches, padlocks, locking FDC plugs, master key retention devices and more. For more information or technical assistance, please call Customer Service at 1-800-552-5669.

## MOUNTING DEVICE TO FLAT MOUNT BRACKET

Use at least four (4), 5/16"-18 x 3/4" length, socket cap screws (provided) to bolt the adapter bracket plate to the existing KeySecure 3b or 4 support bracket. Align adapter bracket slots and insert fasteners through the adapter bracket into the threaded holes in the support bracket and tighten to snug.

## MOUNTING DEVICE TO BRACKET PLATE

Use at least three (3), 1/4"-20 x 1-5/8" length, Grade 8, Hex bolts (provided), to bolt the back plate of the unit through the flat mount bracket onto the support bracket (maximum head height of fasteners: 0.188"). Align brackets and back plate then insert fasteners from the back plate into the support bracket and tighten to snug and Loctite.

***\*Do not place washers on the inside of the back plate.***

Hook the unit onto back plate and insert both #10-32 x 2" length socket cap screws (provided) and tighten to snug. Then insert the Tech Lock and stud into the unit and tighten to snug. Replace the Tech Lock cover and fasten with provided Torx screws.

## ORDERING SPECIFICATIONS

To ensure delivery of the Knox Adapter Plate Kit, Knox suggests using the following specification paragraph:

Knox Adapter Plate Mounting Kit consists of an Adapter Plate, Flat Mount Bracket, and essential hardware.

**Knox Adapter Plate Mounting Bracket constructed of 3/8" solid steel plate:**

**Dimensions:** 5-1/2" H x 5-5/16" W x 3/8" Thick

**Weight:** 3 lbs.

**Finish:** Black Industrial powder coating

**Color:** Black

**Knox Flat Mount Bracket constructed of 1-1/8" solid steel plate:**

**Dimensions:** 5-9/32" H x 3-7/8" W x 1-1/8" Thick

**Weight:** 3 lbs.

**Finish:** Black Industrial powder coating

**Color:** Black

**Adapter Plate Kit**

**P/N:** KLS-AP

**Mfr's Name:** KNOX COMPANY

